

Purflex hoses


Diameter: ø50 - ø450 mm.

Purflex hoses are ideal for use in the chemical and petrochemical industries, for gases, cement dust, granulates, abrasive powders, shavings etc.

They are very hard-wearing and made of 100% polyurethane in a single film layer with welded-in, corrosion protected steel spiral.

Temperature range tolerance from -40°C to +90°C.

Purflex hoses are only available in the length of 5 m.



Dimensional specifications are given in the table below.

Dimensions				
Item no.	Description	D mm	Bending radius mm	Weight kg / m
836505005	Hoses PUR 301 AS	50-51	33	0,280
836506005	Hoses PUR 301 AS	60	38	0,340
836506305	Hoses PUR 301 AS	63-65	40	0,360
836507005	Hoses PUR 301 AS	70	43	0,380
836508005	Hoses PUR 301 AS	80	48	0,440
836509005	Hoses PUR 301 AS	89-90	53	0,480
836510005	Hoses PUR 301 AS	100-102	58	0,510
836512005	Hoses PUR 301 AS	120	68	0,610
836512505	Hoses PUR 301 AS	125-127	71	0,630
836514005	Hoses PUR 301 AS	140	78	0,710
836515005	Hoses PUR 301 AS	150-152	83	0,760
836516005	Hoses PUR 301 AS	160	88	0,810
836518005	Hoses PUR 301 AS	178-180	98	0,900
836520005	Hoses PUR 301 AS	200-203	108	1,030
836522505	Hoses PUR 301 AS	225	122	1,160
836525005	Hoses PUR 301 AS	250	136	1,280
836528005	Hoses PUR 301 AS	280	149	1,430
836530005	Hoses PUR 301 AS	300	159	1,700
836531505	Hoses PUR 301 AS	315	167	1,790
836535005	Hoses PUR 301 AS	350	185	2,000
836540005	Hoses PUR 301 AS	400	210	2,260
836545005	Hoses PUR 301 AS	450	235	2,520
8365125051	Hoses PUR 330 AS	125-127	71	0,820
8365140051	Hoses PUR 330 AS	140	78	0,920
8365160051	Hoses PUR 330 AS	160	88	1,040
8365200051	Hoses PUR 330 AS	200-203	108	1,540